

# X-ray Baggage Inspection System



Fingerprint Login



One Key Turn Off



Baggage Recording



High Resolution  
Color Display



Sound &  
Light Alarm



Multi Energy

The IDT6040B X-ray Security Inspection System is an advanced next-generation solution that combines multiple functions, including intelligent detection, baggage tracking, and high-resolution display. It is well-suited for deployment in environments such as customs, office buildings, large-scale events, courts, prisons, embassies, factories, schools, hospitals, and other public facilities. With a tunnel size designed to accommodate boarding suitcases, small parcels, backpacks, envelopes, and handbags, it ensures efficient and reliable security screening.

- **Material Classification:** Advanced material discrimination technology to recognize different materials and assign different colors (3 or 6 colors).
- **Intelligent Recognition:** Integrated with the advanced detection algorithm, which could detect more than 35 major types of target objects and alarm on them automatically.
- **HD Image:** Integrated with the new generation of image processing system, which could provide with a clearer X-ray image with high resolution.
- **Variable Speed:** One-click to switch the conveyor speed to fit different application scenarios.
- **Remote Management:** Network integration supported real time status, X-ray images, videos, alarm information can be viewed remotely through network, and report can be viewed and downloaded remotely for better management process.

## SPECIFICATIONS

### Dimension

#### Tunnel Dimension

620 mm (W) × 420 mm (H)

#### System Dimension

2011 mm (L) × 887 mm (W) × 1260 mm (H)

## General Specifications

Conveyor Height	600 mm
Conveyor Speed	0.2 m/s, 0.3 m/s, 0.4m/s adjustable
Max. Conveyor Capacity	165 kg (Even Distributed)

## Performance

Wire Resolution	38/40 AWG
Penetration (Steel)	34/36 mm

## X-ray Generator

Number of Generators	1
Anode Voltage / Current	160KV
Cooling / Working cycle	Oil-cooling / Continuous

## Health and Safety

External dose rate	< 0.5 $\mu$ Sv/h (50mm Distance to the Housing)
Film Safe	Guaranteed up to ISO1600

## Detection Algorithm

Prohibited Goods	35 Major Types, over 64 categories
Detection Others	Shield Alarms, etc.

## Integrated Cameras

Cameras	3 Camera, Resolution: 1920x1080 1/2.8"
Sensor Type	Progressive Scan CMOS H.265 / H.264 /
Video Compression Standard	MJPEG

## Installation Data

Power Consumption	< 0.8 KVA
Power Supply	AC 220V (-15% to +10%) , 50Hz/60Hz ( $\pm$ 3Hz); AC 110V (-15% to +10%) , 50Hz/60Hz ( $\pm$ 3Hz);
Noise level	< 60 dB

## Environment

Operating Temperature / Humidity	5°C to 40°C / 5 % to 95 % (non-condensing)
Storage Temperature / Humidity	-20°C to 60°C / 5 % to 95 % ( non-condensing)
Weight	700 Kg

## Additional Features

Image Processing	Color / Black & White(C/B&W), Organic Stripping(ORG-), Inorganic Stripping(INORG-), Negative, High / Low penetration (H/L), Absorptivity increase(ABS+), Absorptivity decrease(ABS-), Super Enhancement(SEN), Edge Enhancement (Edge), 64x seamless zoom in and out, etc.
------------------	---

## Software Functions

Professional TIP system, Operation Intro, Photo and X-ray image connection, etc


Operation Display

21.5 inch

Storage

1,00,000 +

## DIMENSION DRAWING



## ORDER INFORMATION

Part Number

IDT.6040AI



ID TECH SOLUTIONS PVT. LTD.

610, Udyog Vihar Phase-5, Gurgaon, Haryana - 122016, INDIA | T. : +91-124 - 4255530 (6 Lines)

E.: [info@idsolutionsindia.com](mailto:info@idsolutionsindia.com) | W: [www.idsolutionsindia.com](http://www.idsolutionsindia.com)



The product specifications and descriptions listed in the specification sheet are subject to change anytime without notice.

©2025 ID Tech Solutions Pvt. Ltd. All Rights Reserved.